

КАТАЛОГ(КОМПРЕССОРЫ)



ООО ТЛК "СУДОКОМПЛЕКТ"  
ПОСТАВЩИК СУДОВОГО ОБОРУДОВАНИЯ

[www.mor-sk.ru](http://www.mor-sk.ru)

тел+7 920 030 05 75

тел. +7 920 010 00 68

тел.+7 920 060 30 80

E-mail:[avponkin@yandex.ru](mailto:avponkin@yandex.ru)

E-mail:[tlk.sudokomplekt@yandex.ru](mailto:tlk.sudokomplekt@yandex.ru)







## Diesel Portable Air Compressors

1. Cummins or Yuchai engines.
2. the pressure range 1.7-2.4mpa, air discharge pressure range 16-29.5m<sup>3</sup>/min.
3. Automatic control and protection system.
4. Error free capacity control.
5. Deluxe micro-computer fluorescence control panel.
6. All weather models for high altitude operations(customization available for above 5500m high altitude applications by ZEGA only).
7. High quality filtration system with safety filters.
8. Upgraded to EU Stage IIIA engine for more energy saving & eco-friendly.

Model	Nominal Pressure ( Mpa)	F.A.D(Free Air Delivery) ( m <sup>3</sup> /min)	Oil Content	Disel Power Kw(HP)	Weight(wet excl.fuel) ( kg)	Unt Dmensions(overall)LxWxH ( mm)
168SCY-17four wheels	1.7	16	≤6	162(220)	2550	3620X1950X2200
177SCY-17four wheels	1.7	16	≤6	177(240)	3760	3720X1970X2250
181SCY-17two wheels	1.8	17	≤6	181(260)	3650	3600X1870X2660
186SCY-18four wheels	1.8	18	≤6	191(260)	3760	3600X1870X2660
198SCY-18four wheels	1.8	18	≤6	191(260)	3900	3720X1970X2550
250SCY-18four wheels	1.8	23	≤6	295(400)	4800	3810X2000X2900

228SCY-21	2.1 Two stage compression	20	≤6	221(300)	4060	3800X1870X2550
300SCY-24		30	≤6	309(420)	4910	4150X1950X2900
40SCY	0.6	4.2	≤6	37(50)	860	2400X1330X1480
58SCY-8two wheels	0.8	7	≤6	58(80)	1550	3140X1740X1900
110SCY-8four wheels	0.8	12	≤6	110(150)	2180	3120X1630X2290
110SCY-10two wheels	1	12	≤6	110(150)	2130	2890X2020X2270
110SCY-10four wheels	1	12	≤6	110(150)	2180	3120X1630X2290
110SCY-14.5two wheels	1.45	10	≤6	110(150)	2130	2890X2020X2270
110SCY-14.5four wheels	1.45	10	≤6	110(150)	2180	3120X1630X2290
138SCY-14.5two wheels	1.45	13	≤6	140(180)	2384	3350X2060X2350
139SCY-13four wheels(Yuchai)	1.3	15	≤6	140(180)	2580	3650X1700X2040
141SCY-13four wheels(Yuchai)	1.3	15.5	≤6	140(180)	2510	3650X1700X2040
180SCY-8four wheels	0.8	20	≤6	179(240)	3428	3720X1970X2250



## Electric Motor Driven Portable (Open Frame) Screw Air Compressors

- 1.Special design for narrow space applications such as tunnels and subways.
- 2.Easy assembly and disassembly for easy transportation.
- 3.Air cooling or water cooling systems to choose for different environment.
- 4.Super strong protection of power pack for the worst air environment.
- 5.Automatic operation and protection system .
- 6.Super large power capacity for longer life.

SKY Model	Nominal Pressure ( Mpa)	F.A. D m <sup>3</sup> /min	Noise dB ( A)	Outlet Temperature ( °C )	Oil Content ppm	Motor Power Kw(HP)	Weight(wet,excl .fuel) ( kg)	UnitDimension s (overal).LxWx H ( mm)	Drive Mode
22SK Y-6	0.6	4.6	70	≤ environment+8	≤3	22 ( 30 )	550	1900X920X1160	Belt
30SK Y-8	0.8	5	70	≤ environment+8	≤3	30 ( 40 )	550	1900X920X1160	Belt
30SK Y-8	0.8	5	70	≤ environment+8	≤3	30 ( 40 )	550	1900X920X1160	Direct Acting
45SK Y-7	0.7	7	75	≤ environment+8	≤3	45 ( 60 )	850	1900X920X1250	Belt



## SPE(original SDY) Electric Screw Air Compressors

1. heavy-duty SKF bearings, advanced single-stage, or dual stage made for ZEGA oil injected air end.
2. Energy saving full series, class 2 energy efficiency, Extra Large air displacement, more cost saving.
3. Computerized automatic control and protection system.
4. Error free capacity control, unique ZEGA only electrical system with twice the operation range.
5. High quality heavy duty filtration system with safety filters.

Model	Nominal pressure ( Mpa)	F.A.D(Free Air Delivery) ( m <sup>3</sup> /min)	Oil Content	Motor Power Kw(HP)	Weight(wet excl.fuel) ( kg)	Unit Dimensions(overall)LxWxH ( mm )
75SDY-8four wheels	0.8	13.6	≤5	75(100)	1956	2810X1515X1970
75SDY-14.5two wheels	1.45	10	≤5	75(100)	1952	3080X1980X1818
75SDY-10two wheels	1	10	≤5	75(100)	1832	3080X1980X1818
90SDY-8four wheels	0.8	16	≤5	90(120)	2273	2180X1515X1970
90SDY-14.5two wheels	1.45	13	≤5	90(120)	2112	3080X1980X1810

90SDY-14.5four wheels	1.45	13	≤5	90(120)	2273	2180X1515X1920
110SDY-8four wheels	0.8	20	≤5	110(150)	3170	3190X1640X2110
132SDY-8four wheels	0.8	24	≤5	132(180)	3175	3190X1640X2110
132SDY-13four wheels	1.3	17	≤5	132(180)	3175	3190X1640X2110
132SDY-17four wheels	1.7	15	≤5	132(180)	3175	3190X1640X2110
160SDY-13four wheels	1.3	24	≤5	160(220)	3398	3190X1640X2110
185SDY-17four wheels	1.7	19	≤5	185(250)	3398	3190X1640X2110
185SDY-21four wheels	2.1	23	≤5	185(250)	4150	3470X1920X2230





## Diesel stationary screw air compressor special for deep well drilling

1. Cummins or Yuchai engines.
2. Automatic control and protection system.
- 3, no omission of capacity control.
- 4, Error free capacity control.
- 5, All weather models for high altitude operations(customization available for above 5500m high altitude applications by ZEGA only).
- 6, High quality filtration system with safety filters.

Model	Nominal Pressure ( Mpa)	F.A.D(Free Air Delivery) ( m <sup>3</sup> /min)	ppm Oil Content	Diesel PowerKw(HP )	Weight(wet excl.fule) ( kg)	Dimensions(overall),LxWxH ( mm)
S55	1.7	17	≤6	191(260)	3420	3720X1970X2550
S70D China national standard	2.1 Two stage compression	20	≤6	221(300)	3720	3380X1870X2170
S95D	2.3 Two stage compression	27	≤6	295(400)	4270	3660X2000X2500



S100D China national standard	2.4 Two stage compression	29.5	≤6	309(420)	4430	3700X1950X2280
S105D China national standard	2.5 Two stage compression	30	≤6	368(500)	4980	3850X1950X2380
S120D China national standard	2.5 Two stage compression	35	≤6	375(510)	5300	3850X2010X2150